

VH Series **Infra-Red** **Flame Scanners**



	<p>VH32 IR Flame Scanner – Comprising a cast aluminium housing fitted with a 2" BSP nickel plated brass cap nut and plug-in photocell assembly. The standard unit is supplied with 2 metres of armoured cable, with up to 20 metres available as an option. It is suitable for use on all industrial burners firing gas or oil, where discrimination is not essential, and is available in standard and high-temperature (VH32/HT) variants.</p>
	<p>VH102 IR Flame Scanner – A Scanner similar in operation and construction to the VH32 but fitted with a 1 1/4" BSP nickel plated brass cap nut. It is available in standard and high-temperature (VH102/HT) variants.</p>
	<p>VH105 IR Flame Scanner – A Scanner similar in operation and construction to the VH32 but fitted with a 1/2" BSP nickel plated brass cap nut. It is available in standard and high-temperature (VH105/HT) variants.</p>
	<p>VH500 IR Flame Scanner – Comprising a nickel plated copper housing fitted with a 1/2" BSP nickel plated brass cap nut. The unit is of sealed construction, intended for low-cost applications, and cannot be repaired or serviced by the user. The standard unit is supplied with 2 metres of armoured cable, with up to 20 metres available as an option. It is suitable for use on all industrial burners firing gas or oil, where discrimination is not essential, and is available in standard and high-temperature (VH500/HT) variants.</p>